



TECHNICAL DATA SHEET

RIZOL MARATHON MP 3 GREASE

DISCRIPTION RIZOL Marathon MP grease is a Premium quality lithium based all purpose, multifunctional, high temperature, high shear stable, water resistant greases. It also provides excellent protection against rusting and corrosion on its lubricating surfaces.	FEATURES <ul style="list-style-type: none">• Unique Transparent appearance.• Excellent protection against rusting.• Excellent corrosion inhibition property.• Excellent oxidation resistance.• Resists water washout and grease loss due to vibration.
APPLICATIONS : RIZOL Marathon MP is recommended for antifriction and plain bearings in industrial applications. These are widely used in steel plants, cement plants, roller bearings in electric motors and fans and other industrial applications. RIZOL Marathon MP is recommended for all grease-lubricated parts of automobiles including commercial vehicles. The firm consistency and anti-corrosion performance of RIZOL Marathon MP also makes it suitable for bearings fitted to boat trailers.	

TYPICAL PRODUCT DATA

TYPICAL CHARACTERSTICS	UNIT	TEST METHOD	SPECIFICATION
Colour and texture		Visual	AMBER & TRANSPARENT
Thickener			Lithium
NLGI Grade		ASTM D - 217	3
Worked Penetration at 25°C(60X)	10 ⁻	ASTM D - 217	220-250
Drop Point, (min)	°c	ASTM D - 566	180
Copper Strip Corrosion	Rating	ASTM D - 4048	1a
Oxidation Stability ^b 100 Hrs	Kg/cm	ASTM D - 942	0.5
Operating Temperature Range	°c		-15 to +130
Base Oil Viscosity @ 40°C	cSt	ASTM D - 445	130

WARNING :- Do not overfill

NOTE: The values mentioned above are subject to change due to our continued R&D; these are typical values and do not constitute a specification.

Health and Safety: This Grease is not hazardous under normal conditions of use. For further guidance appropriate Material safety Data Sheet may be referred.

RIZOL PETRO PRODUCTS PVT.LTD

PLOT NO. 199, SECTOR 4 - IMT MANESAR, GURUGRAM - HARYANA, INDIA 122050